

Schubantrieb				Motor				
Typ	Hub Max. [mm]	Stellkraft Max. [kN]	Regelkraft <sup>1)</sup> Max. [kN]	Motortyp	Leistung <sup>2)</sup> P [W]	Drehzahl [1/min]	Max. Strom <sup>3)</sup> I <sub>max</sub> [A]	Einschaltstrom <sup>4)</sup> I <sub>max</sub> [A]
SDL 05-11	15	1,0	1,0	sm <sup>5)</sup>	25	750	1,05	1,05
SDL 11-10	35	1,0	1,0	sm <sup>5)</sup>	25	750	1,05	1,05
SDL 11-11	35	2,0	2,0	sm <sup>5)</sup>	25	750	1,05	1,05
SDL 50-10	55	6,0	5,0	sm <sup>5)</sup>	60	450	2,5	2,5
SDL 50-20	55	6,0	4,0	bldc <sup>6)</sup>	60	4 500	2,5	2,5
SDL 50-30	55	4,0	2,5	bldc <sup>6)</sup>	120	4 500	5,0	5,0
SDL 100-20	85	6,0	6,0	bldc <sup>6)</sup>	120	4 500	5,0	5,0
SDL 100-30	85	15	10	bldc <sup>6)</sup>	120	4 500	5,0	5,0

**Hinweise zur Tabelle**

1) Regelkraft	Maximal zulässige Stellkraft im Regelbetrieb
2) Leistung P	Maximale Leistungsaufnahme
3) Max. Strom I <sub>max</sub>	Strom bei maximalem Drehmoment
4) Einschaltstrom I <sub>max</sub>	Maximaler Kurzzeiteinschaltstrom
5)	Schrittmotor
6)	Brushless DC-Motor