

Technical data Part-turn actuators for modulating duty

General information

Part-turn actuators of the SQRV .2 type range with variable operating times. AUMA actuator controls of ACV .2 type are required to change the operating time.

Type	Operating time for 90° [s]	Torque range ¹⁾		Modulating torque ²⁾ Max. [Nm]	Number of starts Starts Max. [1/h]
		Min. [Nm]	Max. ³⁾ [Nm]		
SQRV 05.2	4 – 28	50	150	75	1,500
	12 – 120				
SQRV 07.2	4 – 28	100	300	150	1,500
	12 – 120				
SQRV 10.2	12 – 120	200	600	300	1,500
SQRV 12.2	24 – 240	400	1,200	600	1,500
SQRV 14.2	40 – 360	800	2,400	1,200	1,500

- 1) The tripping torque is adjustable for directions OPEN and CLOSE within the indicated torque range
- 2) Maximum torque for modulating duty
- 3) Maximum torque to approx. 50 % of shortest operating time

Valve attachments and weight

Type	Valve attachment		Valve shaft			Handwheel		Weight approx. [kg]
	Standard EN ISO 5211	Option EN ISO 5211	Cylindrical Max. [mm]	Square Max. [mm]	Two-flat Max. [mm]	Ø [mm]	Turns for 90°	
SQRV 05.2	F05/F07	F10	25.4	22	22	160	11	21 ¹⁾
							16	27 ²⁾
SQRV 07.2	F05/F07	F10	25.4	22	22	160	11	21 ¹⁾
							16	27 ²⁾
SQRV 10.2	F10	F12	38	30	27	200	11	26 ¹⁾
							16	31 ²⁾
SQRV 12.2	F12	F14	50	36	41	200	11	35 ¹⁾
							16	43 ²⁾
SQRV 14.2	F14	F16	60	46	46	200	11	44 ¹⁾
								55 ²⁾

- 1) Indicated weight includes SQRV part-turn actuator with electrical connection in standard version, unbored coupling and handwheel.
- 2) Indicated weight includes SQRV part-turn actuator with electrical connection in standard version, unbored coupling and handwheel, including base and lever.

Features and functions

Type of duty	Intermittent duty S4 - 25 %, class C according to EN 15714-2 For 100 % nominal voltage and +40 °C ambient temperature and at modulating torque load.		
Motors	3-phase AC asynchronous motor, type IM B9 according to IEC 60034-7, IC410 cooling procedure according to IEC 60034-6		
Mains voltage, mains frequency	3-phase AC Voltages/frequencies		
	Volt	220 – 240	380 – 480
	Hz	50 – 60	50 – 60
	1-phase AC Voltages/frequencies		
	Volt	110 – 120	220 – 240
	Hz	50 – 60	50 – 60
	Permissible variation of mains voltage: ±10 % Permissible variation of mains frequency: ±5 %		
Overvoltage category	Category III according to IEC 60364-4-443		
Insulation class	Standard:	F, tropicalized	
	Option:	H, tropicalized	

We reserve the right to alter data according to improvements made. Previous documents become invalid with the issue of this document. For further information on the product, refer to www.auma.com.

Technical data Part-turn actuators for modulating duty

Features and functions	
Motor protection	Standard: Thermoswitches (NC)
	Option: PTC thermistors (according to DIN 44082)
Motor heater (option)	Voltages: 110 – 120 V AC, 220 – 240 V AC or 380 – 480 V AC
	Power: 12.5 W
Swing angle	Standard: Adjustable between 75° and < 105°
	Options: 15° to < 45°, 45° bis < 75°, 105° to < 135°, 135° to < 165°, 165° to < 195°, 195° to < 225°
Self-locking	Yes (Part-turn actuators are self-locking if the valve position cannot be changed from standstill while torque acts upon the output drive.)
Manual operation	Manual drive for setting and emergency operation, handwheel does not rotate during electrical operation.
	Option: Handwheel lockable
	Handwheel stem extension Power tool for emergency operation with square 30 mm or 50 mm
Indication for manual operation (option)	Indication whether manual operation is active/not active via single switch (1 change-over contact)
Electrical connection	Standard: AUMA plug/socket connector with screw-type connection
	Option: Terminals or crimp-type connection Gold-plated control plug (sockets and pins)
Threads for cable entries	Standard: Metric threads
	Option: Pg-threads, NPT-threads, G-threads
Terminal plan	TPA00R100-011-000 (basic version)
Splined coupling for connection to the valve shaft	Standard: Coupling without bore
	Options: Machined coupling with bore and keyway, square bore or bore with two-flats according to EN ISO 5211
Valve attachment	Dimensions according to EN ISO 5211 without spigot

With base and lever (option)

Swing lever	Made of spheroidal cast iron with two or three bores for fixing a lever arrangement. Considering the installation conditions, the lever may be mounted to the output shaft in any desired position.
Ball joints (option)	Two ball joints matching the lever, including lock nuts and two welding nuts, suitable for pipe according to dimension sheet.
Fixing	Base and four holes for fastening screws

Electronic control unit

Non-Intrusive setting	Magnetic limit and torque transmitter (MWG)
Position feedback signal	Via actuator controls
Torque feedback signal	Via actuator controls
Running indication	Blinking signal via actuator controls
Heater in switch compartment	Resistance type heater with 5 W, 24 V AC

Service conditions

Use	Indoor and outdoor use permissible
Mounting position	Any position
Installation altitude	≤ 2,000 m above sea level
	> 2,000 m above sea level on request
Ambient temperature	Standard: –30 °C to +70 °C
	Options: –40 °C to +70 °C
	–60 °C to +60 °C
Humidity	Up to 100 % relative humidity across the entire permissible temperature range

Technical data Part-turn actuators for modulating duty

Service conditions	
Enclosure protection according to EN 60529	Standard: IP68
	Option: DS terminal compartment additionally sealed against interior of actuator (double sealed)
	According to AUMA definition, enclosure protection IP68 meets the following requirements: <ul style="list-style-type: none"> • Depth of water: maximum 8 m head of water • Duration of continuous immersion in water: Max. 96 hours • Up to 10 operations during immersion • Modulating duty is not possible during immersion
Pollution degree according to IEC 60664-1	Pollution degree 4 (when closed), pollution degree 2 (internal)
Corrosion protection	Standard: KS: Suitable for use in areas with high salinity, almost permanent condensation, and high pollution.
	Option: KX: Suitable for use in areas with extremely high salinity, permanent condensation, and high pollution.
Coating	Double layer powder coating Two-component iron-mica combination
Colour	Standard: AUMA silver-grey (similar to RAL 7037)
	Option: Available colours on request
Lifetime	AUMA part-turn actuators meet or exceed the lifetime requirements of EN 15714-2. Detailed information can be provided on request.
Sound pressure level	< 72 dB (A)

Further information	
EU Directives	Machinery Directive 2006/42/EC Low Voltage Directive 2014/35/EU EMC Directive 2014/30/EU RoHS Directive 2011/65/EU RED Directive 2014/53/EU